

NORTHEAST ASPHALT USER / PRODUCER GROUP





Maryland Specification for Using Contractor and Agency Test Results in a Computer-based Pay Factor Program

Larry Michael – MDSHA

- Maryland's Goals
- QC/QA Specification
- MarylandWare
- Pay Factor Program
- HMA View
- Pavement Tools Consortium



Maryland's Goals

- Track HMA Projects
- Life Cycle Costs
- QC/QA Specification Incorporating Contractor and State Results
- Computer Based

QC/QA Specifications

- Mixture
- Density
- Random Sampling



MIXTURE



NEW SPEC

Lot size: 6000 tons

QA Sample Location: Behind the Paver

QC Frequency: As approved in QC plan. Sampling may be from trucks or BTP.

QA Frequency - minimum of 1/day/mix or 1/1000 tons; whichever yields higher frequency.

QA test compared to QC by MSMT 733, t & F tests. If comparable, QC & QA results will be combined to determine final pay factor. If not, only State results will be used.

No incentive











Edit View Insert Format Lools Table Window Help Type a question for help Final showing Markup Show	9-30	DTO10-6CL838B51	.rtf - Microsoft Word											_ 8 :	×
Image: State of the state	Eile	<u>E</u> dit <u>V</u> iew <u>I</u> nsei	rt F <u>o</u> rmat <u>T</u> ools	T <u>a</u> ble <u>W</u> indow	<u>H</u> elp						Тур	ie a quest	ion for hel	p - 3	x
Final Showing Markup • Showing Amrkup		20888	199 Ba Palo	- 🙆 📼 100	%	. » д	rial		• 13	S - B			= = +		>>
Find Showing Markup • Show • • • • • • • • • • • • • • • • • • •													s— •— ·	-,,-	•
Image: Section 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1	Final S	howing Markup 🔹	Show 🕶 🛃 🎲 🋂	' • 🆄 • 🛅 •	1 🕲	📥 🗸									
Mix Type: Gap Grade Mix Band: 12.5 mm Begin Date: 9-30-04 End Date: 10-6-04 Analysis Type: Production Significance Level: 0.01 ** Property Desc Set ** Property 042 ** Property 043 ** Property 043 <tr< td=""><td>L</td><td>8</td><td>1 • • • • • • • 2 •</td><td> 3</td><td></td><td>1</td><td>· 4 ·</td><td>· · I ·</td><td> 5</td><td></td><td> 6</td><td>·</td><td> 7</td><td>- I</td><td>┓</td></tr<>	L	8	1 • • • • • • • 2 •	3		1	· 4 ·	· · I ·	5		6	·	7	- I	┓
Wink Type: Outpoint Mink Type: Outpoint Mink Type: Outpoint Begin Date: 9-30-04 End Date: 10-6-04 Analysis Type: Production Significance Level: 0.01 **	•	Mix Type: Ga	n Grade	1 1		1	1	I	1	1	I.				-
Normal Defaultion 12.5 minin Begin Date: 9.30-04 End Date: 10-6-04 Analysis Type: Production Significance Level: 0.01 ** <tr< td=""><td>•</td><td>Mix Rand: 12</td><td>15 mm</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr<>	•	Mix Rand: 12	15 mm												
Begin Date: 9-30-04 End Date: 10-6-04 Analysis Type: Production Significance Level: 0.01 ** <	~	- Mix Danu, 12 - Regin Doto: (
End Date: 10-0-04 Analysis Type: Production Significance Level: 0.01 **		Degin Date: 3	9-30-04												
Analysis Type: Production Significance Level: 0.01 Property Data Set FTest/Test US LSL N Min Mean Max Standard Dev. PWSL * Presing 230mm QC2+QA2 Pass/Past 12.5 8.5 5 11.5 11.8 12.1 0.23 100 * Passing 4.75mm QC2+QA2 Pass/Past 33 25 10 28 3 30.8 33 11.3 96.05 QA2 Pass/Past 6.9 6.1 5 6.2 6.3 6.4 0.06 100 * VTM QC2+QA2 Pass/Past 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 CMPWSL: 99 Computed Pay Factor: 100 Tonage: 6065.24 Page 1 Sec 1 1/1 At 0.6" Ln 1 Col 1 REC TRK EXT OVE English (U.5	•	End Date: 10	-6-04												
Significance Level: 0.01		Analysis Type	e: Production											- 11	
Image: 1 Property Data Set: FTest/Test US LSL N Min Mean Max Standard Dev. PWSL % Passing QA2 Pass/Fail 12.5 8.5 5 11.5 11.8 12.1 0.23 100 % Passing 1.30mm QC2+QA2 Pass/Pass 22 14 10 18 18.8 20 0.73 100 % Passing 1.75mm QC2+QA2 Pass/Pass 32 10 24.3 30.8 33 133 96.05 AC QA2 Pass/Pass 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 CMPWSL: 99 Computed Pay Factor: 100 Tonage: 6065.24	•	Significance l	Level: 0.01											- 11	
E Property Data Set FTest/TTest US LSL N Main Max Standard Dev. PWSL % Passing QA2 Pass/Pail 12.3 8.5 11.5 11.8 12.1 0.23 100 % Passing 2.30mm QC2+QA2 Pass/Pail 12.3 13.2 10 18 18.8 20 0.73 100 % Passing 4.75mm QC2+QA2 Pass/Pass 33 25 10 28.3 30.8 33 1.33 96.05 AC QA2 Pass/Pass 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 VTM QC2+QA2 Pass/Pass 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 CMPVVSL: 99 Computed Pay Factor: 100 Tonage: 6065.24 *	•													- 11	
Image: Data Set FTest/Test US LSL N Min Meen Max Standard Dev. PWSL ** ** @ A2 Pass/Pass 22 14 10 18 18.8 0.73 100 ** Passing 2.30mm QC2+QA2 Pass/Pass 22 14 10 18 18.8 0.73 100 ** Passing 4.75mm QC2+QA2 Pass/Pass 33 25 10 28.3 30.8 33 1.33 96.05 AC QA2 Pass/Pass 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 VTM QC2+QA2 Pass/Pass 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 CMPWSL: 99 Computed Pay Factor: 100 Image: Image: </td <td>•</td> <td></td> <td>- 11</td> <td></td>	•													- 11	
Property Data Set FTest/Test US LSL N Min Mean Max Standard Dev. PWSL % Passing 236mma QC2+QA2 Pass/Pais 22 14 10 18 18.8 20 0.73 100 % Passing 236mma QC2+QA2 Pass/Pais 22 14 10 18 18.8 20 0.73 100 % Passing 4.75mma QC2+QA2 Pass/Pais 23 30.8 33 1.33 96.05 AC QA2 Pass/Pais 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 VTM QC2+QA2 Pass/Pais 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 Computed Pay Factor: 100 Tonage: 6065.24 * * * * * • • • * * • * * * * * * * * * * * * * * * * * *	- F	+												- 11	
W Passing QA2 Pass/Fail 12.5 8.5 5 11.5 11.8 12.1 0.23 100 W Passing 2.36mm QC2+QA2 Pass/Pass 22 14 10 18 18.8 20 0.73 100 W Passing 4.75mm QC2+QA2 Pass/Pass 33 25 10 28.3 30.8 33 133 96.05 AC QA2 Pass/Pass 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 VTM QC2+QA2 Pass/Pass 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 CMPVVSL: 99 Computed Pay Factor: 100 Tonage: 6065.24 - <td>· ·</td> <td>Property</td> <td>Data Set</td> <td>FTest/TTest</td> <td>US</td> <td>LSL</td> <td>N</td> <td>Min</td> <td>Mean</td> <td>Max</td> <td>Standard Dev.</td> <td>PWSL</td> <td></td> <td>- 11</td> <td></td>	· ·	Property	Data Set	FTest/TTest	US	LSL	N	Min	Mean	Max	Standard Dev.	PWSL		- 11	
• • Passing 2.30mm QC2+QA2 Pass/Pass 22 14 10 18 18.8 20 0.73 100 • • Passing 2.30mm QC2+QA2 Pass/Pass 33 25 10 28.3 30.8 33 1.33 96.05 AC QA2 Pass/Pass 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 VTM QC2+QA2 Pass/Pass 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 CMPVVSL: 99 Computed Pay Factor: 100 Tonage: 6065.24		% Passing	QA2	Pass/Fail	12.5	8.5	5	11.5	11.8	12.1	0.23	100			
W Pessing *7.1mm QC3*Qra Pess/Pail 6.9 6.1 5 6.2 6.3 6.4 0.06 0.07 93.06 * QC2+QA2 Pess/Pess 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 CMPWSL: 99 Computed Pay Factor: 100 Computed Pay Factor: 100 Tonage: 6065.24	•	% Passing 2.36mm	QC2+QA2	Pass/Pass Decc/Decc	22	14	10	18	18.8	20	0.73	100			
VTM QC2+QA2 Pass/Pass 4.7 2.3 10 2.4 3.4 4.8 0.7 93.06 CMPWSL: 99 Computed Pay Factor: 100 Computed Pay Factor: 100 Image: 6065.24	· +	AC	QC2+QA2 QA2	Pass/Fail	6.9	6.1	5	20.3 6.2	6.3	6.4	0.06	100			
CMPWSL: 99 Computed Pay Factor: 100 Tonage: 6065.24 \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare		VTM	QC2+QA2	Pass/Pass	4.7	2.3	10	2.4	3.4	4.8	0.7	93.06			
CMPWSL: 99 Computed Pay Factor: 100 Tonage: 6065.24	•														
CMPWSL: 99 Computed Pay Factor: 100 Tonage: 6065.24 $\blacksquare \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare$	1														
Computed Pay Factor: 100 Tonage: 6065.24 $\blacksquare \blacksquare \blacksquare \blacksquare \blacksquare$ $D_{\underline{r}aw \lor k} A\underline{u}toShapes \lor \land \land \blacksquare \bigcirc \blacksquare \blacktriangleleft \textcircled \land \blacksquare \land \blacksquare \land \blacksquare \land \blacksquare \land \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare$ Page 1 Sec 1 1/1 At 0.6" Ln 1 Col 1 REC TRK EXT OVR English (U.5		CMPWSE 99	a												
Tonage: 6065.24 $\blacksquare \square \square \blacksquare \blacksquare$ $Dr_{aw} \bullet \bigcirc$ AutoShapes $\bullet \land \land \frown \bigcirc \blacksquare \blacksquare \blacksquare \textcircled{\colored} @ \bullet \checkmark \blacksquare \frown \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare \blacksquare$ $Page 1 Sec 1 1/1 At 0.6" Ln 1 Col 1 REC TRK EXT OVR English (U.5)$	•	Computed D	- av Eactor: 100												
$ \overrightarrow{r} = \mathsf$	ທ		ay Factor, 100 5 04												
$\begin{array}{c} \bullet\\ $		Tonage, 606;	5.24												-
$\begin{array}{c} \bullet \\ \bullet \\ \bullet \\ \bullet \\ \bullet \\ \end{array}$ $\equiv \Box \blacksquare \blacksquare \blacksquare \\ \bullet \\ \hline \\ D\underline{r}aw \bullet \\ \hline \\ Page 1 \\ Sec 1 \\ 1/1 \\ At 0.6" \\ Ln 1 \\ Col 1 \\ REC \\ TK \\ EXT \\ OVR \\ English (U.S \\ \hline \\ U.S \\ \hline \\ \end{array}$	•														±
· ■ □ □ □ ▲ Dr_aw • R AutoShapes • \ \ D O O A CI I REC TRK EXT OVR English (U.S)	-														0
$\equiv \Box \Box \Box = \Box$ $Dr_{aw} \bullet \downarrow$ $AutoShapes \bullet \setminus \land \Box \bigcirc \blacksquare 4 3 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2$															Ŧ
Dr_aw ▼ $\boxed{>}$ AutoShapes ▼ $\boxed{>}$ $\boxed{>}$ $\boxed{\bigcirc}$ $\boxed{]$ $\boxed{\bigcirc}$ $\boxed{]$ $\boxed{]}$ \boxed	≣ ធ 🛛														
Page 1 Sec 1 1/1 At 0.6" Ln 1 Col 1 REC TRK EXT OVR English (U.S	D <u>r</u> aw •	- 🗟 AutoShapes	• \ \ 🗆 🗆 🗎] 🖪 🛟 🙍 🛛	8 3	- 🏼	- A	- =	₩ ₽		-				
	Page	1 Sec 1	1/1 At 0.6"	Ln 1 Col 1	RE	C TRK	EXT	OVR E	English (U.	S					
🗃 Start 🛛 🏹 🙈 🥔 🗌 🔥 Maryl 🛛 📴 Micros 🖗 Novell 🖓 Shovell 🖓 Mail F 🕅 9-30 T 🚺 🕵 🔊 🕅 🖓 🖓 🖓 🖓 🖓 👘 10:11 AM	Sta	rt 🛛 📶 🚙 🥔	Maryl	aryl		Novell.		Mail F	1 1 1 1 1 1 1 1 1 1	ат	🐠 🖽 N 🌬	<i>⊘</i> № 0	<mark>)</mark> 跚 11	0:11 AM	

DENSITY



NEW SPEC

QC - core or nuclear testing

QC - one test per 500 tons or 5 per day

QA - one core required per 500 tons or 5 per day

QA core results used to develop pay factors. QC core results may be used as well.

t & F tests used for Acceptance / Pay

Testing frequency based on paving production. Use Behind Paver Gravities

Pay adjustments by lot based on average density and minimum value

Incentive allowed

DENSE GRADED MIXES Percent of Maximum Density

Lot Average	No Sublot Below	Pay Factor %
Within 94.0 – 97.0	94.0	105
Within 94.0 – 97.0	93.0	104
Within 93.0 – 97.0	93.0	103
Within 93.0 – 97.0	92.0	102
Within 92.0 – 97.0	92.0	101
Within 92.0 – 97.0	91.0	100
Within 91.0 – 97.0	90.0	95
Within 90.0 – 97.0	90.0	90
Within 89.0 – 97.0	89.0	85
Less than 89.0		75.0 or rejected at Engineer's discretion

GAP - GRADED MIXES Percent of Maximum Density

Lot Average	No Sublot Below	Pay Factor %
Within 95.0 – 97.0	95.0	105
Within 95.0 – 97.0	94.0	104
Within 94.0 – 97.0	94.0	103
Within 94.0 – 97.0	93.0	100
Within 93.0 – 97.0	92.0	95
Within 92.0 – 97.0	91.0	90
Within 91.0 – 97.0	90.0	85
Less than 91.0		75.0 or rejected at Engineer's discretion



🛃 Start

1

 \bigotimes



🛛 🖉 Welcome to t... 🛛 🗞 Novell Group... 📴 Presentation ... 🔛 Maryland W... 🏾 🏴 N 🕅 🖉 🌾 🕅 🎲 🚮

6:55 AM





-4-04CL838B51.rtf - Microsoft Word	
<u>E</u> dit <u>V</u> iew Insert Format <u>T</u> ools T <u>a</u> ble <u>W</u> indow <u>H</u> elp	Type a question for help \checkmark X
🚔 🔄 🎒 🎒 🐧 🖤 🖻 🛍 🗠 - 🍓 📰 100% 🔹 🦉 Arial 🔹 13.5 - 🖪 🛽 🖳	│≣≣¦≣∃≣∉∉"
Showing Markup 🔹 Show 🔹 🌚 🌚 🚽 🤣 👻 🍆 🖕 🏠 🖕	
· · · · · · · · · · · · · · · · · · ·	* * * 👌 * * * 7 * * * 👘 👗
Mix Type: Gap Grade Mix Band: 12.5 mm Significance Level: 0.01	

Property	Data Set	FTest/TTest	US	LSL	N	Min	Mean	Max	Standard Dev.
% Density (Core)	(QC3+QA3)/2	Pass/Pass	0	0	5	95.2	95.6	96	0.35

QA Data

Test	Lot	Sublot	Activity	Test. Value
1	9	1	3	94.6
2	9	2	3	94.8
3	9	3	3	96.2
4	9	4	3	96.1
5	9	5	3	95

QC Data

Test	Lot	Sublot	Activity	Test Value
1	9	1	3	96
2	9	2	3	95.6
3	9	3	3	95.4
4	9	4	3	96
5	9	5	3	96.4

	<u>ا</u> ت							
•	\triangleright	A <u>u</u> toShapes •	• <	$\mathbf{A} \Box \mathbf{O}$	₫ 4	ः 🙎 🔜	🆄 • 🚄 • 📥 • ≡ 🚍 🚍 🗃 💣 ₊	
1		Sec 1	1/2	At 0.6"	Ln 1	Col 1	REC TRK EXT OVR English (U.S	
art		🚮 🥭 💋	^	Maryl	Maryl	C Micros	🚱 Novell 🔄 Mail F 🕅 10-4 🛛 🕀 🖿 N 😪 🖉 🕼 🖼	10:37 AM

▼ ±

٥

📴 10-4-04CL838B51.rtf - Microsoft Word	
Edit Yiew Insert Format Tools Table Window Help Type a question for help	• ×
🗋 😂 🖶 🔩 🥔 🖤 🖻 🛍 🗠 - 🍓 🚾 100% - 🌺 Arial 🛛 - 7.5 - 🖪 🖌 🖳 🚍 🗄 🗄 🛱	* * *
Final Showing Markup 🔹 Show 🔹 🌚 🌚 🚽 🖘 🏷 🔹 🏠 🖕	
■ . Z	
* Indicates Outlier Test Value	
Density Data Used for Pay Factor Calculations	
- Density Data Osed for Flag actor Calculations	
- Test Sub-Lot Mean - 1 95.3	
2 95.2 3 95.8	
- <u>4 96</u> - <u>5 95.7</u>	
Use (QC3+QA3)/2 Data to Compute Pay Factor	
Computed Pay Factor: 105	
Tonage: 1504.67	
-	
o	
·	× ±
	0 ∓
	Þ
Draw 🔹 😓 🗛 🛨 🗩 💫 💭 🖓 🎒 🎝 🎝 🖓 🗸 🖉 🗸 🗸 🗸 🗸 🗮 🗮 🗮 🎒 🗸	
Page 1 Sec 1 1/2 At 8" Ln 49 Col 1 REC TRK EXT OVR English (U.S	
🏽 🔀 Start 🔢 🧭 🏈 🔄 👫 Mar 🔛 Mar 📴 Micr 🧐 Nov 🖓 Mail 👘 10 🔍 🍕 💾 N 🕍 🖉 🕅 🎁 10:3	9 AM





RECENT PROJECTS

Status	Project #	Last Update
Active	AL698B51	9/24/2002 12:18:00 PM
Complete	PG2665177	1/11/2001
Complete	CE7805177	12/6/2000
Complete	WA9205177	11/14/2000
Complete	<u>H07965176</u>	10/26/2000

More...

Disclaimer | Terms of Service © 2000-2002. All Rights Reserved.



👌 Internet

8:34 AM

©®�€₽N೫๖₽₽₽\$

















Superpave 12.5 mm SR21 Vic. To Ritzville, 1 WA Completed on 10/27/2001

PROJECT INFO MIX DESIGN CONSTRUCTION PERFORMANCE ANALYSIS

đΧ

Field Control Charts Diagnostics





Superpave 12.5 mm SR21 Vic. To Ritzville, 1 WA Completed on 10/27/2001

PROJECT INFO MIX DESIGN CONSTRUCTION PERFORMANCE ANALYSIS

đΧ

Field Control Charts Diagnostics







Interactive Pavement Guide

ē

Start 🚮

This document (or "Guide" for short) is a multimedia CD-ROM based document whose primary purpose is to provide a general pavement overview covering all aspects from materials to design to construction to maintenance. It functions both as a learning tool and a ready reference; users can learn about pavements as well as use it as a reference to look up typical values, methods, practices and resources.

Preview the Interactive Pavement Guide at: http://hotmix.ce.washington.edu/wsdot_web

Novell GroupWise - Mailbox

The version on the web for preview is a WSDOT-specifc version. A general CD-ROM based version for member use is planned for late 2004. This version will not have state-specific information in it, but will have the PTC logo and be oriented towards member agencies. A brief summary of the proposed Interactive Pavement Guide work plan is as follows:

- Late 2004: Produce CD-ROM version for PTC members. Information will not be state-specific. We anticipate producing several master CD-ROMs and then distributing them to members. Member agencies can then choose to reproduce this CD-ROM.
- 2005: Convert the CD-ROM version to an entirely web-based version. This will effectively divorce content (the pictures, videos, animations and text) from delivery (the "look and feel" of the site like the title bar and green borders in the picture below). This content will then be divided up into small discreet "chunks" (e.g., a page on stone matrix asphalt) that the user can select to view. Viewing is customized to user specifications. For instance, if Maryland is viewing, the border and title bar and SHA logo would appear around the information. Users can select one bit of content to view or can set up an entire list of content to be viewed. In this way, one could enter the site and set up a list of content to be viewed by field

🥝 Internet



Simulations - Microsoft Internet Explorer				_ B ×
File Edit View Favorites Tools Help				<u>111</u>
🖙 Back 👻 🤿 🚽 🙆 🚰 🛛 🥘 Search 🛛 🙀 Favorites 🖉 Media	🎯 🗳 🥔 🗹 - 🗐 -			
Address 🙆 http://hotmix.ce.washington.edu/ptc/Default.aspx?tabid=43			• c	≻Go Links ≫
PTC Pavement Tools Consortium				*
Home About Us → PTC Tools Calendar News & Info	Meetings Discussion	Downloads	Gloria Burke	Logout
You are in: PTC Tools 🔸 Simulations	Gainesville, FL '04	7	1onday, October (04, 2004

X Pactor

X Pactor is a Virtual Hotmix Compactor Simulation that is designed to allow users to experience hot mix rolling through their computer. It also provides a realistic simulation of hot mix cooling physics through the use of the MultiCool software. The ultimate goal is to bring cost-effective interactive 3D training environments to contractors, state and federal agencies. The X Pactor is the first product toward that goal.

-





PMSView is an Internet application that allows pavement related data to be accessed and analyzed from any geographic location through a straightforward navigation and display scheme on a web browser. PMSView extends beyond the typical pavement management boundary by providing the ability to incorporate pavement design, construction, and usage data into the interface. PMSView can be populated through a wide variety of electronic data sources, including spreadsheets, existing databases and mainframes, map-based spatial data, among others.

Birthol - with these raises and second types	200
The ER day familier Task Add	
Opti-O-M # 6 [lint glass @ to 0 []-1	13-12-13
	CONTRACTOR OF STREET, STRE
MATTERIALS LABORATORY	
Mark Roder 51 Roder 52 Roder 700 Rod	and Internet
Roadway Brackare	
	ACR
	Dustived Discent Report to Represent Sciences
Area 12 and 12 a	Acces Acces
Empire IP-	1475
Terrar Int	Callen:
	N DOM SHOND
al inte	Sectors



